



ALLEGION™

**SCHLAGE**

## Schlage Touch™

**We're doing more than just throwing away the key.**

**We're making it obsolete.** Because no key means no more fumbling in your pockets or digging around your purse. It also means Schlage Touch™ is 100% pick-proof and bump-proof. All in a low-profile design that's incredibly sleek and—since it's a Schlage—incredibly strong.

Sorry, keys, but it's better this way.



## SCHLAGE TOUCH ELECTRONIC DEADBOLT SPECS



## BE375 specs

Certification	ANSI/BHMA Grade 2
Product Dimensions (w x h x d)	(w x h x d) 3" x 5.4" x 5.2"
Weight	3.4 lbs
Warranty	3 year electronics; limited lifetime mechanical finish
Battery	9V battery (1)
Latch Throw	1"
Cylinder	None
Door Thickness	1 3/8" to 1 3/4"; thick door kit extends 1 7/8" to 2 1/2"
Cross Bore Minimum	2 1/8"
Edge Bore	1"
Latch/Backset	2 3/8" or 2 3/4" adjustable
Latch Faceplate	1" x 2 1/4"
Latch Faceplate Options	round corner, square corner, and drive-in (dual option standard)
Strike	1 1/8" x 2 3/4" round corners, strike reinforce
Keys	none
Codes	2 pre-set, unique, four-digit user code, storage of up to 19 user codes
Operating Temperatures	Outside lock body (exterior mounted): -35C to 66C Inside lock body (interior mounted): -10C to 50C

## SCHLAGE TOUCH ELECTRONIC LEVER SPECS



\* Broadway Lever also available in 625 Bright Chrome, 626 Satin Chrome and 716 Aged Bronze.

## FE695 specs

<b>Certification</b>	ANSI/BHMA Grade 2
<b>Product Dimensions (w x h x d)</b>	(w x h x d) 3" x 5.4" x 7.9"
<b>Weight</b>	4.5 lbs
<b>Warranty</b>	3 year electronics; limited lifetime mechanical and finish
<b>Battery</b>	9V battery (1)
<b>Lock</b>	7/8" housing diameter, 1/2" throw
<b>Cylinder</b>	None
<b>Door Thickness</b>	1 3/8" to 1 3/4"; thick door kit extends 1 7/8" to 2 1/2"
<b>Cross Bore Minimum</b>	2 1/8"
<b>Latch Faceplate Size</b>	1" x 2 1/4" radius corner
<b>Latch Faceplate Options</b>	Springlatch radius corner and circular drive-in faceplates
<b>Strike</b>	1 5/8" x 2 1/4", radius corner, full lip latch strikes
<b>Keys</b>	none
<b>Codes</b>	2 pre-set unique four-digit user codes, storage of up to 19 user codes 900
<b>Operating Temperatures</b>	Outside lock body (exterior mounted): -35C to 66C Inside lock body (interior mounted): -10C to 50C

## SCHLAGE TOUCH ELECTRONIC LEVER SPECS

### CAMELOT



505  
Bright  
Brass,  
Flair Lever



619  
Satin  
Nickel,  
Flair Lever



622  
Matte  
Black,  
Flair Lever

\* Flair Lever also available in 609 Antique Brass, 626 Satin Chrome and 716 Aged Bronze.



619  
Satin  
Nickel,  
Accent  
Lever



622  
Matte  
Black,  
Accent  
Lever



716  
Aged  
Bronze,  
Accent  
Lever

\* Accent Lever also available in 505 Bright Brass, 609 Antique Brass, 625 Bright Chrome and 626 Satin Chrome.

## FE695 specs

Certification	ANSI/BHMA Grade 2
Product Dimensions (w x h x d)	(w x h x d) 3" x 5.4" x 7.9"
Weight	4.5 lbs
Warranty	3 year electronics; limited lifetime mechanical and finish
Battery	9V battery (1)
Lock	7/8" housing diameter, 1/2" throw
Cylinder	None
Door Thickness	1 3/8" to 1 3/4"; thick door kit extends 1 7/8" to 2 1/2"
Cross Bore Minimum	2 1/8"
Latch Faceplate Size	1" x 2 1/4" radius corner
Latch Faceplate Options	Springlatch radius corner and circular drive-in faceplates
Strike	1 5/8" x 2 1/4", radius corner, full lip latch strikes
Keys	none
Codes	2 pre-set unique four-digit user codes, storage of up to 19 user codes 900
Operating Temperatures	Outside lock body (exterior mounted): -35C to 66C Inside lock body (interior mounted): -10C to 50C

### About Allegion

Allegion (NYSE: ALLE) helps keep people safe and secure where they live, work and visit. A \$2 billion leading provider of security products and solutions, Allegion offers products under 23 brands in more than 120 countries. Allegion's portfolio includes CISA®, Interflex®, LCN®, Schlage® and Von Duprin®. For more, visit [allegion.com](http://allegion.com)

aptiQ ■ LCN ■ SCHLAGE ■ STEELCRAFT ■ VON DUPRIN



© 2014 Allegion  
MR5010  
[allegion.com](http://allegion.com)